



# ASF series

## Solar Storage Inverter

ASF4880SH3  
ASF48100SH3

ASF48120SH3



### Efficient

- Advanced MPPT technology with up to 99.9% efficiency
- Up to 800V PV input voltage, ideal for high power

### User-friendly

- Industrial design with a modern aesthetic look
- Wall-mounted installation saves home space

### All-in-one

- The 400V three-phase system is efficient, reliable and ideal for large equipment, providing energy and cost saving

### Reliable

- Outputs high quality pure sine wave AC power
- 8-12kW load power to meet the needs of most households

### Safety

- 360 degrees of security from hardware to software
- IEC, FCC and other safety approvals

### Intelligent

- Exclusive Li-ion battery BMS dual activation
- Time-slot function to save cost with peak-valley tariffs

MODEL	ASF4880SH3	ASF48100SH3	ASF48120SH3	Can Be Set
<b>INVERTER OUTPUT</b>				
Rated Output Power	8,000W	10,000W	12,000W	
Max. Peak Power	16,000W	20,000W	24,000W	
Rated Output Voltage	230/400Vac(three-phase)			✓
Capacity of Motor Load	5HP	6HP	6HP	
Rated Frequency	50/60Hz			✓
Output Waveform	pure sine wave			
Switching Time	10ms (typical)			
<b>BATTERY</b>				
Battery Types	Li-ion / Lead-Acid / User Defined			✓
Rated Battery Voltage	48Vdc			
Voltage Range	40~60Vdc			✓
Max. PV Charging Current	180A	220A	260A	✓
Max. Utility / Generator Charging Current	100A	120A	120A	✓
Max. Hybrid Charging Current	180A	220A	260A	✓
<b>PV INPUT</b>				
No. of MPPT	2			
Max. Input Power	6,000W/6,000W	7,500W/7,500W	9,000W/9,000W	
Max. Input Current	22A/22A			
Max. Open-circuit Voltage	800Vdc/800Vdc			
MPPT Operating Voltage Range	200~650Vdc/200~650Vdc			
<b>UTILITY / GENERATOR INPUT</b>				
Input Voltage Range	phase voltage 170~280V, line voltage 305~485V			
Input Frequency Range	50/60Hz			
Bypass Overload Current	63A			
<b>EFFICIENCY</b>				
MPPT Tracking Efficiency	99.9%			
Max. Battery Inverter Efficiency	≥92%			
European Efficiency	97.2%	97.5%	97.5%	
<b>GENERAL</b>				
Dimensions	620*445*130mm (2.03*1.46*0.43ft)			
Weight	27kg (59.52lb)			
Protection Degree	IP20, indoor only			
Ambient Temp	-10~55°C, >45°C derated			
Noise	<60dB			
Cooling Method	air cooling			
Warranty	2 years			
<b>COMMUNICATION</b>				
Internal Interface	RS485 / CAN / USB / Dry contact			✓
External Module (optional)	Wi-Fi / GPRS			✓
<b>CERTIFICATION</b>				
Safety	IEC62109-1, IEC62109-2, UL1741			
EMC	EN61000-6-1, EN61000-6-3, FCC15 classB			
RoHS	Yes			