

ABOUT SRNE

- $\hfill \square$ SRNE 15 years in PV industry, committed to independent R&D and production.
- ☐ Holds over 200 patents in energy storage, with unique industry—leading technologies.
- ☐ Chooses top-quality international components to deliver high-value products to customers.
- ☐ Upholds values of customer priority, proactivity, responsibility, and innovative breakthroughs.

SRNE Solar Co,.ltd. www.srnesolar.com





MODEL			HF4830S	660–145
INVERTER OUTPUT				
Rated Output Power		3,300W		
Max.Peak Power		6,600VA		
Rated Output Voltage		230Vac (Single-Phase)		
Load Motor Capacity		2HP		
Rated Frequency		50/60Hz		
Waveform		Pure sine wave		
Switch Time		10ms (typical)		
BATTERY				
Battery Type		Lead-Acid / Li-ion / User-Define		
Rated Battery Voltage		48V		
Battery Volatge Range		40~60Vdc		
Max. Solar Charging Current		60A		
Max. Grid/Generator Charging Current		60A		
Max. Hybrid Charging Current		120A		
SOLAR INPUT				
No. Of MPPT		1		
Max.PV Array Power		3,400W		
Max. Input Current		40A		
Max. Open Circuit Voltage		145Vdc		
MPPT Voltage Range		60~115Vdc		
GRID/GENERATOR INPUT				
Input Voltage Range		170~280Vac		
Input Frequency Range		50/60Hz		
Bypass Overload Current		30A		
EFFICIENCY				
MPPT Tracking Efficiency		99.9%		
Max. Efficiency		92%		
GENERAL DATA				
Dimension	37	8*280*103mm	Moisture	0~100%
Weight		6.2 kg	Cooling Method	Fan Cooling
Protection Degree	IP2	20 Only Indoor	Warranty	2 years
Temperature		–15°C~55°C	Communication	RS485/CAN/USB/Dry Contac
External Module (Optional)	١	Wi-Fi/GPRS	Topology	Transformerless
Certificate		s/EN61000/FCC F ification	Part15 ClassB/IEC 62109/IE	EC 62040/IEC 62477/SAA/PSE Circular

PROTECTION

Equipped with PV current limit and power limit protection, PV night anti-reverse charging protection, utility input over-voltage protection, utility input under-voltage protection, battery over-voltage protection, battery under-voltage protection, load output short-circuit protection, radiator over-temperature protection, over-load protection, PV anti-reverse protection, AC back-filling protection, bypass overcurrent protection, battery input overcurrent protection, battery input protection, charging short-circuit protection,.